

MUSTANG SPECIFICATION

‘MUSTANG®’ 125mm O.G. CONTINUOUS PRE-PAINTED GUTTER SYSTEM.

‘Mustang®’ continuous gutter and fittings (**British Board of Agrément Certificate No 91/2625**) in pre-coated 0.9mm thick 3105 H45 aluminium. Profile to be 125 x 97mm O.G. section. Material to be pre-coated both sides in Hydrocoat / Textured NH 800 in Black/Brown/White/Green/Cream* (**British Board of Agrément Certificate No 93/2918**) Detail Sheet and Hydro Aluminium Alucoat Letter of Quality Assurance) Installation to be carried out only by an approved contractor (details available from A.R.P Ltd) with material supplied by A.R.P, Ltd. Gutter to be formed on site in continuous lengths and secured and supported with extruded mill finish aluminium fixing support bracket .16mm wide x 2.5mm thick at 450mm centres. Corners. Stop Ends, Straight Connectors, 60mm/70mm Leaf Traps* are formed using ‘Mustang®’ Polycarbonate fittings sealed with ‘Mustang®’ “Mustseal” silicone sealant. The gutters are to be fixed using M4 x 40mm Stainless steel countersunk screws.

All to be supplied by Aluminium Roofline Products Ltd.

* Delete as appropriate

